

Nig. J. Pure & Appl. Sci. Vol. 35 (Issue 2, 2022) e-ISSN 2756-4045 (C) 2022 Faculty of Physical Sciences and Faculty of Life Sciences, Univ. of Ilorin, Nigeria www.njpas.com.ng



Physico-Chemical Properties of Cross-linked and Hydroxypropyl White Sorghum (sorghum bicolor) Starch

*¹Ogundiran, O. O., ²Ogundiran, A. A. and ³Afolabi T. A.

Page | 4375

¹Department of Chemistry Tai Solarin College of Education Omu-Ijebu, Ogun State ²Department of Chemical Sciences, Tai Solarin University of Education, Ijagun, Ogun State ³Department of Chemistry, Federal University of Agriculture, Abeokuta, Ogun State.

Date Received: 22-03-2022 Date Accepted: 13-07-2022 DOI: https://doi.org/10.48198/NJPAS/22.A15

ABSTRACT

The study investigated the effects of cross-linking and hydroxypropylation on some physico-chemical properties of white sorghum *(sorghum bicolor)* starch. The sorghum starch (NSS) was isolated and chemically modified by hydroxypropylation with propylene oxide and by cross-linking with epichlorohydrin. The swelling, solubility and other physico-chemical properties of the starch was determined. The pasting property and the granule morphology of the starches were also determined using Rapid Visco-Analyzer and Scanning Electron Microscope respectively. Changes in chemical structure of the starch molecule were confirmed by FT-IR. The amylose content (27.01%) of the native sorghum starch decreased after modifications to (20.11 and 18.81) % for cross-linked, and hydroxylpropyl sorghum starches while the starch solubility and swelling increased in the temperature range (50 – 90°C), with the native starch having the highest values. Hydroxylpropyl sorghum starch (PSS) however has better swelling power in all the temperature range when compared with cross-linked sorghum starch (CSS). The shape of the starch granules was mainly spherical and polygonal with various diameters ranging from 6 to 22 μ m, however modification does not have any pronounced effect on the starch granules. Hydroxypropylation reduced the breakdown viscosity of the native sorghum starch from 1630 to 1048 RVU, the peak viscosity of sorghum starch decreased from 2779 RVU for the native starch (NSS) to 2731 RVU in CSS. In conclusion, the modifications employed improved the physiochemical properties of sorghum starch and hence the modified starch could be used industrially.

Keywords: Sorghum, Modification, Swelling, Starch, Granules

Introduction

Starch is the major carbohydrate storage material in many higher plants, and after cellulose, the second largest natural biopolymer. Among food carbohydrates, starch occupies a unique position. It contributes to the physico-chemical properties of food products made from cereals, tubers, roots, legumes, and fruits (Amaraweera *et al.*, 2021; Ammala *et al.*, 2011). Starch is formed during the process of photosynthesis in green plant (Blilck *et al.*, 2010). In human nutrition, it is the basic source of energy for the majority of the world's population, it plays a key role in supplying the metabolic energy that enables the body to perform



© 2022 Creative Common License Attribution 4.0 International

its different functions and it is one of the most important raw materials used in industries.

Starch, a renewable biopolymer, is cheap, readily available and has wide application in various industries for food and non food applications

Page | 4376 industries for food and non-food applications. However, the native form of starch has some limitations in its physico-chemical properties thereby reducing its wide industrial applications. Native starch contains many hydroxyls group which are hydrophilic in nature, resulting in its moisture sensitivity. Due to amorphous (amylose) regions, starch exhibits low mechanical properties such as low tensile strength, elongation at break and brittleness (Amaraweera *et al.*, 2021). Physicochemical properties of starch mainly depend on the amylose and amylopectin ratio.

> Hence, modification is often carried out in order to reduce these limitations. This is based on the fact that various industries where starch is applicable require specific functional properties to get the desired end product. In modification, the properties of starch is improved upon to meet the requirement of end user, giving rise to a range of specialty products. Consequently, starch can be modified by physical, chemical, or enzymatic methods to promote specific functional properties (Krithika and Ratnamala 2010; Jacobs and Delcour 1998).

> However, the origin of starch plays significant role in its physico-chemical properties (Amaraweera et al., 2021; Singh et al., 2011). It can be gotten from several botanical sources including potato, maize, sorghum, cassava, yam, rice etc wheat. (Adebowale et al., 2005). Corn starch is one of the most popular cereal starches widely used in the industry and account for about 60% of the industrial starch used worldwide. Other cereal starch sources with industrial appeal include wheat, rice, etc (Singh et al., 2011). Nevertheless, there are some lesser-known cereals with promising potentials for the industrial application of its starch. One of such cereal is sorghum. Sorghum is a grass specie cultivated for its grain, it

can grow under various environmental stresses and is very eco-friendly (Singh *et al.*, 2011).

Starch is one of the major industrial raw materials in plastic, food, cosmetics, textiles, adhesives,

pharmaceutical and paper industry. The demand for starch as raw material for food and non-food industry in Nigeria is rapidly increasing, this demand is currently being met largely by importation of starch from other countries; the major challenges arising from this are high cost, inadequate supply, late deliveries and transit damages. These problems can be solved by exploiting locally grown crops with good adaptations and yield efficiency as an alternative; cereal such as *sorghum bicolor* could offer this opportunity.

This study was undertaken to exploit the unique characteristics of the starch from *sorghum bicolor*. The physico-chemical, functional and structural properties of the starch were investigated.

Materials and Methods

Proximate analysis of sorghum starch

The starch was isolated using the method of Afolabi, (2012). Moisture content of the starch was determined with a moisture analyzer (Perten-Tecmaster). Ash, crude protein, carbohydrate, and lipid contents were determined according to Ranganna, (1987).

Determination of Amylose content of sorghum starch

The method of Juliano, (1971) was employed with slight modification. 100 mg of the starch sample was weighed into a 100 mL volumetric flask. Approximately 1ml of 95 % ethanol and 9 mL of 1 N NaOH was added to gelatinize the sample and liberate amylose respectively. Iodine solution (2 mL) was added to form amylose-iodine complex and the absorbance was read at a wavelength of 620 nm (PG instruments, T60-U UV-visible spectrophotometer, USA) Standard starch solution containing 0, 20, 40, 60, 80, 100 % amylose was prepared and transmittance read at 620 nm and standard graph plotted. Amylose content of the sample was then determined with reference to the standard curve and expressed on percentage basis.

Hydroxypropylation of sorghum starch

The native sorghum starch (100 g) was weighed into 500 mL screw cap jar and 200 ml distilled water was added followed by the addition of 20 g of Na₂SO₄. The slurry was mixed for 30 min and the pH was adjusted to 11.5 with 1 M aqueous NaOH, 40 ml of propylene oxide was added and the suspension was mixed thoroughly while the jar is closed. The reaction was allowed to proceed at $40^{\circ}C$ for 24 h. The starch suspension was neutralized with dil. HCl (0.1M) and the slurry was centrifuged for 15 min at 10,000 rpm. The starch cake obtained was washed with distilled water until it gave a negative sulphate reaction with BaCl₂. The propyl starch was dried in an oven at $40^{\circ}C$ to 10% moisture content and kept in a sealed container.

Cross-linking of sorghum starch

Native sorghum starch was weighed (100 g) and suspended in 60 mL of distilled water, it was agitated for 2 h using high speed impeller, 2 mL of epichlorohydrin was added and the pH was adjusted to 10.5 with NaOH. The mixture was stirred for 24 h at room temperature using magnetic stirrer. At the expiration of the 24 h period the pH of the slurry was adjusted to 5.5 with acetic acid, filtered and washed with distilled water and subsequently washed with 80 % acetone. The cross-linked starch was dried in an oven at 40°C for 48 h to constant weight. It was then stored in a sealed container.

Determination of solubility and swelling power of sorghum starch

The starch (1.0 g) was dispersed in 50 mL of distilled water; it was manually shaken and heated in a water bath at 50, 60, 70, 80 and 90 °C for 30

min, it was then cooled to 30 °C and centrifuged at 500 rpm for 15 min. The supernatant clear liquid was carefully transferred to a container of specified weight and dried at 110 °C for 4 h. The centrifuge tubes were weighed along with the sediments deposited in them after the supernatant was removed. After drying, the samples were weighed. The swelling power and water solubility index were determined using the relations below (Abdorreza *et al.*, 2012):

Swelling power =
$$\frac{\text{Weight of sediment}}{\text{Sample weight -Weight of soluble}} \times 100$$
(1)
Solubility (%) = $\frac{\text{Weight of soluble}}{\text{Weight of sample}} \times 100$
(2)

Characterization by Fourier transformed infrared (FT-IR) spectroscopy

The FT-IR spectra of unmodified and modified starches were obtained using Perkin Elmer spectrum one spectrometer coupled to an Auto Image light microscope. Spectra were taken with a resolution of 2 cm⁻¹. Samples were thoroughly grounded with exhaustively dried KBr and pellets were prepared by compression under vacuum (Rajan and Emilia, 2006).

Pasting properties of sorghum starches

The pasting properties were measured using Rapid visco analyzer (Perten RVA Tec master version 633). 2.5 g of starch samples were dispersed in 25 mL distilled water, mixed in the RVA Aluminium sample bin thoroughly and was then fitted into the RVA. The slurry was heated from 50°C to 95°C at a rate of 1.5°C/min by means of a thermoregulator. At 95°C the sample was held constant for 20 min (first holding period) while being stirred continuously. The paste was cooled to 50°C at 1.5°C/min and held at that temperature for 15 min (second holding period). The RVA recorded the viscosity continuously as each were reached. Final viscosity, trough, breakdown, setback viscosity, peak time and pasting temperature were read from the pasting profile.

Morphology of sorghum starches

Granule morphology of the starches was studied
by Scanning Electron Microscopy (SEM).
Samples were sputter-coated with Au/Pd using a
vacuum evaporator and examined using a
scanning electron microscope at 10 kV
accelerating voltage using the secondary electron
techniques (Reddy and Bhotmange, 2013).

Results

Proximate composition of sorghum starch

The proximate composition of sorghum starch is presented in Table 1. Moisture content of the sorghum starch ranges from 8.39 % -12.27%. The moisture content increased on modification to 9.38 % (PSS) to 12.27 % (CSS). The moisture level is within the level (maximum 13.50 %) recommended for safe storage (Abdullah et al., 2000). When moisture content is high it could lead to microbial growth with subsequent deterioration in quality of the starch (Moothy 2002). The protein content of the starches ranges from (8.34 to 9.3), 9.34 % protein content for native starch is close to 9.50 % reported by (Awika and Rooney 2004), but higher than a number of cereals (usually below 8 %), which suggest why sorghum is considered suitable as weaning or food supplement for infants.

The amylose content of NSS (27.10 %) is higher than the value for corn starch and most cereals (Ma and Li 2011). The amylose content reduced after modification of the starch. The reduction may be due to breaking of covalent linkages by thermal degradation, and also as a result of amylose leaching. Reduction in amylose content after chemical modification of cereal starches was also reported by (Singh *et. al.*, 2011; Chung and Liu 2009; Lu *et. al.*, 1997) for sorghum, rice and corn starches respectively. FT-IR analysis of sorghum starch

The infra-red spectra for native (NSS) and modified sorghum starches are shown in Figures 1(a-c). The characteristic absorption frequency for starch include; O-H stretching (3214 - 3976) cm⁻¹, C-H stretching (1250 - 900) cm⁻¹. Three characteristic peaks between 998 and 1150 cm⁻¹ are attributed to C-O bond stretching; The peak around 2930 cm⁻¹ is attributed to CH₂ symmetrical stretching vibration, while the peak at 1642 cm⁻¹ is assigned to scissoring of two O-H bonds of absorbed water molecules. A new peak at 1119 cm⁻¹ was observed in the PSS spectra (Figure 1c). The peak at 999 cm⁻¹ is associated with ether group and the intensity of the band after hydroxypropylation show that the functional groups which have a C-O-C ether linkage are newly formed. The band at 1012 cm⁻¹ in figure 1b is associated to an ester group which confirms cross-linking reaction in CSS. This is because both ether and ester groups exhibited strong intensity absorptions near 1000 - 1300 cm⁻¹. Woggum et al. (2014) reported that peaks at these ranges are sensitive to moisture. The peak at 1242 cm⁻¹ corresponds to CH₃ deformation vibration of the ester moiety (Tupa et. al., 2015; Woggum et al., 2014). Changes in chemical structure of the starch molecule were confirmed.

Swelling power and Solubility of the Starch

The results of the swelling power and solubility of the sorghum starch is shown in Table 2. The swelling power of native and modified sorghum starches increased with increase in temperature from 50–90 °C. The swelling power increased from 3.21 to 9.61 for NSS, 3.05 to 5.05 for CSS and 3.55 to 8.08 for PSS. The swelling power of starches was in two-stage process, an initial slow swelling at a temperature range 50–60 °C followed by a significant increased swelling power as the temperature range of 60–90 °C. Hydroxylpropyl sorghum starch (PSS) had highest swelling power in the temperature range (50 - 90) °C compared with the native and cross-linked sorghum starch (CSS). The enhanced swelling capacity with

increase in temperature of the starch is as a result of increased water penetration into the amorphous region of the starch granule as temperature increased (Olayinka et. al., 2008). Increase in swelling power of a starch makes it suitable to be Page | 4379 used as a disintegrant in the pharmaceutical

industry (Chowdary and Enturi, 2011).

The solubility of the native and modified starches also increased as the temperature increased which indicates the dependence of solubility on temperature. The solubility increased from 3.21 to 9.61 for NSS, 3.05 to 5.05 for CSS and 3.55 to 8.08 for PSS. Increase in the starch hydrophilicity after modification facilitated water percolation into the starch granules which is capable of enhancing leaching of amylose granules from the amorphous region. Cross-linked starch exhibit lower solubility than native starch because cross-linking strengthens the boundaries between the starch chains thereby causing an increase in the resistance of the granules (Sun et al., 2013; da Rosa Zavareze and Dias 2011). Cross-linking adds treatment intra and intermolecular bonds at random locations in the starch granule that stabilize and strengthen the granule (Hoover et. al., 2010).

The observed increase in starch solubility as the temperature increased suggests higher amylose contents due to amylose leaching during heating process (Lawal 2004).

Pasting Properties of sorghum starch

The peak viscosity of sorghum starch decreased from 2779 RVU for the native starch (NSS) to 2731 RVU in CSS. Reduction in peak viscosity and cold paste viscosity following modification is a direct result of structural reorganization within the granule of the modified starches. Enhancement of crystallinity after modification limits the starch swelling and structural disintegrations which contribute to starch viscosity in a significant way. These observations are in agreement with similar reports on other starches such as pigeon pea, smooth pea, and rice. (Puncha-arnon and Uttapap 2013; da Rosa Zavareze et. al., 2012).

Nig. J. Pure & Appl. Sci. Vol. 35 (Issue 2, 2022)

Furthermore, set-back value, which is the difference between final viscosity and peak viscosity follows the order PSS > CSS > NSS. The maximum viscosity at a given concentration reflects the ability of the granule to swell freely prior to the physical breakdown. Starches that are capable of swelling to a high degree are also less resistant to breakdown. The decrease in breakdown value recorded can be attributed to the degradation of the starch granules, which further reduced the degree of cross-linking among the starch molecules (Hooover et. al., 2010).

The pasting temperature of CSS is higher than that of PSS, cross-linking increased the peak viscosity owing to increased swelling power. The substitution of the bulky functional group interferes with the nature of inter-molecular binding forces present between the starch chains and thereby weakens the starch granules. Surface erosion of the starch granule after modification may further ease the process of gelatinization. Breakdown viscosity reflects the resistance of starch granules against heat and shear; hydroxypropylation increased breakdown viscosity as compared to CSS, because degradation of amylose chains within amorphous regions of starch granule results in increased solubilisation of starch polymer. Ali and Hasnain, (2013) also reported significant reduction in the breakdown viscosity of white sorghum after modification. The pasting profiles of the starches are presented in Figures 2(a-c). Antarlina, et al, (2021) classified viscosity patterns from Brabendar amylograph as follows; Type A; high swelling starches that show a high pasting peak followed by rapid and major thinning during cooking. Type B; moderate swelling starches that show lower pasting peak and much less thinning; Type C; restricted swelling starches that show no pasting peak by high viscosity that remains constant or increases during cooking; Type D; highly restricted swelling starches that do not swell sufficiently to give a

viscous paste when cooked at normal concentrations. Based on these classifications PSS are similar to Type B (characteristic of normal cereal starches), while CSS is Type C (characteristic of cross-linked or legume starches).

Page | 4380

Morphology of sorghum starch granules

The results of scanning electron microscope (SEM) are presented in Figure 3 (a-c). The starch granules are mainly spherical and polygonal in shape with various sizes ranging from 6 - 22 μ m. Pores are visible on the surface of the granules and the surface of the starch granule appears smooth. No damage was observed, suggesting that the method of extraction did not cause any significant damage to the starch granule. Singh *et al.* (2011) also reported the presence of pores on the surface of sorghum starches. Similar pores were reported on the surface of maize and millet starch granules (da Rosa Zavareze *et. al.*, 2012).

The alkaline environment during the hydroxypropylation process accounts for the

structural changes. This result also suggests that starch crystallinity was altered and allowed the etherifying agents to have more access to the starch molecules. Changes in appearance of starch granules after hydroxypropylation have also been reported for pigeon pea starch. However, no change in surface and shape characteristics was observed.

Table	1:	Proximate	composition	of	native	and
modifi	ed s	sorghum sta	rches			

	NSS	CSS	PSS
Ash content (%)	0.45 ± 0.02	$0.43\pm\!\!0.01$	$0.35\pm\!\!0.08$
Moisture content (%)	8.39 ± 0.00	12.27 ± 0.07	9.38 ± 0.07
Fat content (%)	1.65 ± 0.01	$1.62\pm\!\!0.01$	$1.64 \pm \! 0.08$
Protein content (%)	9.34 ± 0.00	8.41 ± 0.00	8.35 ± 0.07
Crude fibre (%)	2.96 ± 0.01	$2.72\pm\!\!0.01$	2.61 ± 0.01
Carbohydrate Content (%)	79.01 ± 0.01	68.51 ± 0.01	65.06 ± 0.06
Amylose content (%)	$27.10\pm\!\!0.00$	20.11 ± 0.07	18.81 ± 0.01

NSS- native sorghum starch, PSS – hydroxypropylated sorghum starch, CSS – cross-linked sorghum starch

Sample/ T(°C)	50	60	70	80	90
Swelling power					
NSS	3.55 ± 0.02	4.35 ± 0.02	5.66 ± 0.00	7.05 ± 0.00	8.08 ± 0.01
CSS	3.05 ± 0.00	3.68 ± 0.01	4.25 ± 0.01	$4.77 \pm \! 0.01$	5.05 ± 0.02
PSS	3.21 ± 0.01	4.31 ± 0.02	5.21 ± 0.02	9.11 ±0.01	9.61 ±0.23
Solubility					
NSS	2.88 ± 0.23	$2.97 \pm \! 0.01$	4.11 ±0.23	5.04 ± 0.01	5.76 ± 0.00
CSS	2.21 ± 0.02	2.75 ± 0.00	3.45 ± 0.01	$3.87 \pm \! 0.01$	$4.75\pm\!\!0.00$
PSS	2.08 ± 0.01	2.82 ± 0.23	5.15 ± 0.01	6.15 ± 0.01	8.17 ±0.23

Table 2: Swelling and Solubility of native and modified sorghum starches

NSS- native sorghum starch, PSS – hydroxypropylated sorghum starch, CSS – crosslinked sorghum starch



Fig 1: FT-IR Spectra of (a) native starch, (b) cross-linked starch and (c) Hydroxylpropyl starch





Fig 2: Pasting profiles of (a) native starch, (b) cross-linked starch and (c) hydroxypropyl starch



Fig 3: SEM of (a) native sorghum, (b) cross-linked and (c) hydroxylpropyl sorghum starch

Conclusion

The study focused on the effect of modification on the physio-chemical, functional and pasting properties of sorghum starch. From the results, cross-linking and hydroxypropylation of the sorghum starch significantly improved the physicochemical and pasting properties of the starch. Swelling and solubility of the starch reduced significantly after modification, it was observed that temperature had significant effect on the swelling capacity and solubility of the starches. The pasting properties were also affected with the reduction in final viscosity, setback and breakdown values after modification. These properties of the modified starches studied indicate that the starches may be suitable in various industrial applications such as in food products as a thickening agent, stabilizer or emulsifier and in pharmaceuticals as

carriers for controlled release of drugs and bioactive agents.

Competing Interest

There is no conflict of interest

References

- Abdorreza, M., Robal, M., Cheng, L., Tajul, A., & Karim, A. (2012). Physicochemical, thermal, and rheological properties of acidhydrolyzed sago (Metroxylon Sagu) starch. LWT-Food Science and Technology, 46(1), 135–141.
- Abdullah, N., Nawawi, A. & Othman, I. (2000). Fungal spoilage of starch-based foods in relation to its water activity (aw). *Journal of Stored Produce Resources* 36, 47–54.

Adebowale, K. O., Afolabi, T. A., & Olu-Owolabi, B. I. (2005). Hydrothermal treatments of Finger millet (Eleusine coracana) starch. *Food Hydrocolloids*, 19(6), 974-983.

Page | 4383

- Afolabi, T. A. (2012). Synthesis and physicochemical properties of carboxymethylated Bambara groundnut (Voandzeia subterranean) starch. *International journal of food science* & technology, 47(3), 445-451.
- Ali, T. M., & Hasnain, A. (2014). Morphological, physicochemical, and pasting properties of modified white sorghum (Sorghum bicolor) starch. *International journal of food* properties, 17(3), 523-535.
- Amaraweera. S. М., Gunathilake. С., Gunawardene, O. H., Fernando, N. M., Wanninayaka, D. B., Dassanayake, R. S., & Manipura, A. (2021). Development of starch-based materials using current modification techniques and their applications: A Review. Molecules, 26(22), 6880.
- Ammala, A., Bateman, S., Dean, K., Petinakis, E., Sangwan, P., Wong, S., & Leong, K. H. (2011). An overview of degradable and biodegradable polyolefins. *Progress in Polymer Science*, 36(8), 1015-1049.
- Antarlina, S.S., Estiasih, T., Zubaidah, E. & Harijono (2021). The physicochemical properties of white sorghum (Sorghum bicolor L.) flour in various particle sizes by soaking the seeds before and after dehulling. *Food Research*, 5(3), 129-143.
- Awika, J. M., & Rooney, L. W. (2004). Sorghum phytochemicals and their potential impact on human health. *Phytochemistry*, 65(9), 1199-1221.

- Banks, W., & Greenwood, C. T. (1975). Starch and its Components.
- Bilck, A. P., Grossmann, M. V., & Yamashita, F. (2010). Biodegradable mulch films for strawberry production. *Polymer testing*, 29(4), 471-476.
- Chowdary, K. P. R., & Enturi, V. (2011). Preparation, characterization and evaluation of starch citrate- a new modified starch as a disintegrant in tablet formulations. *International Journal of Pharmaceutical Resources and Development*. 12(2), 9 – 17.
- Chung, H. J., & Liu, Q. (2009). Impact of molecular structure of amylopectin and amylose on amylose chain association during cooling. *Carbohydrate Polymers*, 77(4), 807-815.
- Da Rosa Zavareze, E., & Dias, A. R. G. (2011). Impact of heat-moisture treatment and annealing in starches: A review. *Carbohydrate polymers*, 83(2), 317-328.
- Da Rosa Zavareze, E., Pinto, V. Z., Klein, B., El Halal, S. L. M., Elias, M. C., Prentice-Hernández, C., & Dias, A. R. G. (2012).
 Development of oxidised and heatmoisture treated potato starch film. *Food chemistry*, 132(1), 344-350.
- Hoover, R., Hughes, T., Chung, H. J., & Liu, Q. (2010). Composition, molecular structure, properties, and modification of pulse starches: A review. *Food research international*, 43(2), 399-413.
- Jacobs, H., & Delcour, J. A. (1998). Hydrothermal modifications of granular starch, with retention of the granular structure: A review. *Journal of agricultural and food chemistry*, 46(8), 2895-2905.

- Juliano, B. O. (1971). A simplified assay for milled rice amylose. *Cereal Sci. Today*, 16, 334-360.
- Krithika, P. L., & Ratnamala, K. V. (2019).
- Page | 4384Modifiction of Starch: A Review of Various
Techniques. International Journal of
Research and Analytical Reviews, 6(1), 32-
45.
 - Lu, S., Chen, L. N., & Lii, C. Y. (1997). Correlations between the fine structure, physicochemical properties, and retrogradation of amylopectins from Taiwan rice varieties. *Cereal Chemistry*, 74(1), 34-39.
 - Ma, Y., & Li, D. (2011). Impact of enzymatic hydrolysis on the crystal structure, and thermal and textural properties of corn starch. *African Journal of Biotechnology*, *10*(17), 3430-3435.
 - Moorthy, S. N. (2002). Physicochemical and functional properties of tropical tuber starches: a review. *Starch-Stärke*, *54*(12), 559-592.
 - Olayinka, O. O., Adebowale, K. O., & Olu-Owolabi, B. I. (2008). Effect of heatmoisture treatment on physicochemical properties of white sorghum starch. *Food hydrocolloids*, 22(2), 225-230.
 - Puncha-arnon, S., & Uttapap, D. (2013). Rice starch vs. rice flour: Differences in their properties when modified by heat-moisture treatment. *Carbohydrate polymers*, 91(1), 85-91.
 - Rajan, A. & Emilia, A. (2006). Enzymatic modification of cassava starch by bacterial lipase. Bioprocess Biosystem Engineering, 29(1), 65-71.

- Ranganna, S. (1987). Handbook of analysis and quality control for fruit and vegetable products, New Delhi, India: Tata McGraw Hill.
- Reddy, K. & Bhotmange, M. (2013). Isolation of starch from rice and its morphological study using scanning electron microscopy. International Journal of Agriculture and Food Science Technology, 4(9), 859-866
- Singh, H., Chang, Y. H., Lin, J. H., Singh, N., & Singh, N. (2011). Influence of heat– moisture treatment and annealing on functional properties of sorghum starch. *Food Research International*, 44(9), 2949-2954.
- Sun, Q., Sun, C., & Xiong, L. (2013). Mechanical, barrier and morphological properties of pea starch and peanut protein isolate blend films. *Carbohydrate polymers*, 98(1), 630-637.
- Tupa, M. V., Ramírez, J. A. Á., Vázquez, A., & Foresti, M. L. (2015). Organocatalytic acetylation of starch: Effect of reaction conditions on DS and characterisation of esterified granules. *Food chemistry*, 170, 295-302.
- Woggum, T., Sirivongpaisal, P., & Wittaya, T. (2014). Properties and characteristics of dual-modified rice starch based biodegradable films. *International journal* of biological macromolecules, 67, 490-502.